

3.6V/7.2V Screwdriver with Torque Control



Chuck size	□ 1/4" Hex Quick Change	
Max.torque	High: 2.0 N-m Low: 6.0 N-m	
Speed at no load	High: 0~900 rpm Low: 0~300 rpm	
Clutch torque (approx.)	High: 0.3 N-m-2.0 N-m (stage 1-10, 0.19 N-m per stage) Low: 0.3 N-m-4.0 N-m (stage 1-21, 0.19 N-m per stage)	
Charging time	Usable: 35 minutes, Full: 60 minutes (Battery pack EY9L20, charger EY0L20)	
Weight (incl.battery)	630g	
Size (LxHxW)	145mm x 198mm x 42mm	
Max. screws driving	High mode: M4 screw Low mode: M5 screw	
Working capacity	Fastening	Screws in Sheet Metal (M2.5 x 6mm) High: Approx.1900 pcs Screws in Sheet Metal (M4 x 10mm) High: Approx.1850 pcs Screws in Sheet Metal (M5 x 8mm) Low: Approx.1450 pcs
Standard accessory	EYFEA1N2S 2 X 1.5Ah Li-Ion battery pack (EY9L20) Charger (EY0L20) Clutch & H/L switch lock cover EYFEA1N Clutch & H/L switch lock cover	
Function	<ul style="list-style-type: none"> • Auto Shut-Off Function • Auto-Power Stop Function • LED Light • Clutch & H/L switch lock cover • Electronic brake • ESD approved (as per EN 55014-1 and -2) 	

<Accessory>

1.5Ah Li-Ion Battery Pack EY9L20B	Charger EY0L20B

7.2V screw driver achieves high speed screw driving with high accuracy

Compact and Light Weight

User-friendly size and weight of EYFEA1N can reduce operator fatigue. Well balanced T shape body and slim grip also improve operator acceptance.



Clutch & High/Low switch lock cover
Clutch & High/Low switch lock cover prevents the operator from changing clutch setting or RPM setting by mistake.



LED light
Operation in dimly lit areas is improved with the built in LED light.

