

Blind rivet setting tool

RivBee® PF-Series



Premium Power Tools



MADE IN GERMANY



HS-Technik GmbH
High - System - Technik

RivBee® PF-Series

Programmable battery blind rivet tool with force sensor

- 25 mm device stroke
- Nose assembly with quick-change system
- Nose assemblies for Koenig expander available
- Adapter for Huck / Arconic / GageBilt / available
- Handle vibration alarm
- OLED-Display
- Intelligent battery management
- Brushless high-power motor
- Collection container monitoring
- Contact pressure sensor
- LED to illuminate the application area
- Recuperation extends the battery service time
- Service counter for preventive maintenance
- Blind rivet counter
- Recovery (counter memory function)
- 100 individual programs
- Process and quality documentation with current/stroke curve
- At least 150,000 results incl. setting curves are saved in the tool
- Optional: Barcode reader and Wi-Fi
- Process and quality documentation with force/stroke curve
- Force sensor, precision class $\leq 0.5\%$



For more information about other RivBee models, tool structure and accessories click here!

Technical data

| Model | max. setting force | Setting speed | Dimensions L x W x H | Weight | max. mandrel \varnothing | Remark |
|--------------|---------------------|---------------|--|-----------------------|----------------------------|---|
| RBPF-15* | 15 kN (3370 lbf) | 47 mm/sec. | 302 x 73 x 270 mm (11.88 x 2.87 x 10.63 in) | 1.70 kg (3.75 lbs) | 4.5 mm (0.18 in) | incl. pressure sensor & nose assembly 60 mm |
| RBPF-20* | 20 kN (4496 lbf) | 37 mm/sec. | 302 x 73 x 270 mm (11.88 x 2.87 x 10.63 in) | 1.70 kg (3.75 lbs) | 6.3 mm (0.25 in) | incl. pressure sensor & nose assembly 60 mm |
| RBPF-15*SFC1 | 15 kN (3370 lbf) | 47 mm/sec. | 302 x 73 x 270 mm (11.88 x 2.87 x 10.63 in) | 1.70 kg (3.75 lbs) | 4.5 mm (0.18 in) | incl. pressure sensor & nose assembly SFC |
| RBPF-20*SFC4 | 20 kN (4496 lbf) | 37 mm/sec. | 302 x 73 x 270 mm (11.88 x 2.87 x 10.63 in) | 1.70 kg (3.75 lbs) | 6.3 mm (0.25 in) | w/o pressure sensor & incl. nose assembly SFC |
| RBPF-15*HU | 15 kN (3370 lbf) | 47 mm/sec. | 302 x 73 x 270 mm (11.88 x 2.87 x 10.63 in) | 1.70 kg (3.75 lbs) | 4.5 mm (0.18 in) | without nose assembly & pressure sensor |
| RBPF-20*HU | 20 kN (4496 lbf) | 37 mm/sec. | 302 x 73 x 270 mm (11.88 x 2.87 x 10.63 in) | 1.70 kg (3.75 lbs) | 6.3 mm (0.25 in) | without nose assembly & pressure sensor |

*W = Wi-Fi option

*B = Barcode reader option

*WB = Wi-Fi & barcode reader option

SFCx = SFC expander nose assembly

HU = Adapter for Huck/Arconic/Gage Bilt nose assembly**

**There is no guarantee that all traction heads from the manufacturer's named will fit.
Dimensions and weights without nose assembly and battery.
Delivered without nose piece, battery and charger.



HS-Technik GmbH
High - System - Technik

Im Martelacker 12
D-79588 Efringen-Kirchen
Phone: +49 (0) 76 28 - 91 11-0
Fax: +49 (0) 76 28 - 91 11-90
E-mail: info@hs-technik.com
Internet: www.hs-technik.com

© Copyright June 2021

Subject to modifications and errors. All figures are non-binding.

We reserve the right to make technical changes to our products and the range of products as a result of further development.

Reproduction and the use of texts, even excerpts of our brochures is prohibited and will be prosecuted.